



TECHNICAL SPECIFICATIONS

Max Rated Speed	5,150 RPM
Angular Momentum at Max Rated RPM	40,000 N-M-S
Anti-Rolling Torque at Max Rated RPM	104,720 N-M
Spool-up Time to Max Rated RPM	70 minutes (5,150 RPM)
Spool-up Time to Stabilization	49 minutes (4,378 RPM)
Spool-up Power	
Spool-Up Power	5000 Watts
Operating Power	1,900 - 4,400 Watts
Operating Power Input	208-230 VAC @ 30 Amps, 50/60 Hz
Control Power	240 Watts Max
Control Power Input	24 VDC @ 15 Amps Max
Seawater Pump Power Input	24 VDC @ 20 Amps Max
Sea Water Supply to Heat Exchanger	13 GPM (49 LPM) Minimum 15 GPM (57 LPM) Maximum
Weight	4,074 lb (1,848 kg)
Envelope Dimensions	54.3 L x 55.9 W x 40.6 H (inches) 1.38 L x 1.42 W x 1.04 H (meters)
Noise Output	<73 dBC @ 3.3 feet (1 meter)
Ambient Air Temperature	32F - 140F (0C - 60C)

Marine Service Asia offers the details of this device in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the device.